

DESCRIPTION

ConcretePaint is a two-component cement-based paint, consisting of a can of cement-based powder, special high hardness and resistance plus a colored mixing resin, breathable and high hardness coating.

It can be supplied in different particle sizes to achieve more or less anti-skidding.

There are three particle sizes, coarse, medium or fine, the thicker the particle the more anti-skid.

Once the ConcretePaint is dry, apply FinishPaint water-based sealer for the protection of the coating. This finish sealer adds surface hardness to the system and gives it a satin finish. This product is developed primarily for rehabilitating discolored or white printed concrete where the protective resin has been affected by moisture affected by rising damp, the main feature of ConcretePaint is that it is highly permeability that allows the evaporation of water vapor by capillarity.

CHEMICAL-PHYSICAL TECHNICAL CHARACTERISTICS

- **FINISH:** matte
- **DILUTION:** Ready to use
- **SHINE LEVEL:** matte
- **SEALER FINISH:** satin finish
- **DRYING TIME:** 2 hours
- **SHELF LIFE:** 1 year from date of production in original unopened containers.
- **STORAGE:** The temperature should not be lower than + - 5o and higher than + - 25o during storage.
- **APPROXIMATE YIELD:** 0.5kg/m² per coat.

MAIN PROPERTIES

- Breathable
- Non-yellowing
- Easy application and cleaning Water based.
- Moderate elasticity
- No odor.
- Very good adhesion
- Roller application
- Setting by resin and cement.

FIELDS OF APPLICATION

ConcretePaint is a two-component coating for concrete and printed pavements, garage ramps, etc.

APPLICATION

Mix the powder with the resin in equal parts, wait approximately 15 minutes once the mixture is poured, spread with a roller, brush or soft bristle brush on the surface to be painted.

Once dry apply FinishPaint to water to give a more satin look.

TECHNICAL DATA

- **Finish:** Matte
- **Specific Weight (kg/lt):** 1.6
- **Viscosity (sec.for-4):** 1min for 4
- **Working temperature (oC):** 15o-25o
- **Yield:** 0.5kg/m² + -
- **Touch dry:** 30min
- **Total drying:** 24hs
- **Solubility and cleaning:** Water
- **Colors:** Ral (check availability)

FORMATS

20 kgs containers comp - A powder 20 liters containers comp - B resin
5 kgs packages comp - A powder 5 liters packages comp - B resin

STORAGE

1 year in original container.

C/Reina Elionor 25-27 • 08205 Sabadell (Barcelona)
T. (+34) 977 079 111 • info@ecoresinas.com • ecoresinas.com

