

DESCRIPTION

One-component primer in aqueous dispersion acrylic-polyurethane aliphatic polyether based. Easy and quick to apply by roller or brush. Very good anchorage on different types of substrates (concrete pavements, microcement, rasilla catalana, etc.) Suitable as a primer for transparent sealing on the outside, it does not yellow due to the action of UV rays. Not recommended as a finish.

TECHNICAL DATA

PRODUCT SPECIFICATION	
Density	1,00 - 1,05 gr./cc.
Color	Transparent
Appearance	Opalescent liquid
Content	solid 22,5% by weight
CHARACTERISTICS OF DRY PRIMER	
Appearance	Tack-Free Glossy
Color	Colorless

APPLICATION

Brush or roller.

SUPPORT

All materials normally used in construction, clean and dry. Not suitable for non-porous substrates.

DILUTION

Product to use, does not require dilution.

DRYING

Recoating 1-3hs depending on the temperature and relative humidity of the environment, and absorption of the support.

APPLICATION CONDITIONS

Apply at ambient and substrate temperatures between +10 and 30 oC. Do not apply with relative humidity above 70 %. The substrate temperature should be at least 3 oC higher than the dew point.

WARNINGS

- Do not use the product at -5oC and +30oC.
- Stir the product with an electric stirrer before use.
- Do not leave the containers open for a long time.
- Do not use products that intervene in the system if they are not recommended in writing by Ecoresinas.
- Do not add water or additives to the product.
- Do not accelerate the drying process with heaters during the days after application until curing.

CLEANING

The tools should be cleaned with water within 120 minutes of use, after which mechanical means should be used thereafter.

PACKAGE FORMAT

1kg 2kg 5kg

STORAGE

Containers should be stored in cool, dry rooms for a maximum of 12 months. The product should be kept in its original closed container, keeping the manufacturer's reference, product name, batch number and safety labels.

Containers should be stored in cool, dry rooms for a maximum of 12 months. The product should be kept in its original closed container, keeping the manufacturer's reference, product name, batch number and safety labels.