

### DESCRIPTION

It is a water-based resin, with excellent adhesion on any surface with little or no porosity, and a permanent residual tack that ensures adhesion between coats. It has a high elasticity, maintaining this property for long periods of time with a high resistance to water and alkalis, so it resists excellently the different atmospheric conditions.

### RECOMMENDED APPLICATIONS

- Bonding bridge between finishes and low porosity surfaces.
- Bonding bridge between tiles, stoneware, and mortars.
- Bonding bridge between old walls and new applications
- Increasing the bond between old walls and new applications.
- Filling of small cracks to absorb the dilatations of the construction.
- Fixing of earthy and crumbling surfaces.
- Waterproofing of facades

### TECHNICAL CHARACTERISTICS

- **Appearance:** White liquid
- **Density:** 1± .04 gr /cm<sup>3</sup>
- **Application temperature:** +0 oC to +30 oC
- **Toxicity / Flammability:** No

### APPLICATION

For applications on smooth, slightly porous finishes, it should be used undiluted. For porous surfaces can be diluted 20%-30% with water and apply several coats.

### PERFORMANCE

Depends on the absorption of the substrate.

### RECOMMENDATIONS TO BE TAKEN INTO ACCOUNT DURING THE APPLICATION PROCESS

It is essential to use protective glasses and gloves during the application and mixing process. mixing process. If the product comes into contact with the eyes, wash them immediately with plenty of water and seek medical attention.

### CLEANING

The tools should be cleaned with water within 30 minutes of use, after that, mechanical means should be used.

### PRESENTATION

PrimerQuarz is available in 1kg and 5kg containers.

### STORAGE

At least 12 months in original containers in a dry and protected environment.