

DESCRIPTION

Thixotropic coating for walls and floors, to be used as a decorative element in interior surfaces. Gel Metallic Effect is a monocomponent agramase made with water based polyurethane resin, thixotropic agents, and metallized mica particles. It can be used as a decorative effect glaze, mixing colors or without dilution, applied by trowel as a metallic stucco. Gel Metallic Effect is a waterproof coating for walls and floors subsequently protected with Finish W TRP on walls or Finish W TRP Radiant on floors.

ASPECT

Shiny, Satin, Matte

MIX

Shiny

MIXTURE

- As a glaze: 1 part Metallic Effect Gel - 3 parts water
- As a filler: As used

APPLICATION

- As a glaze: Sponge
- As a filler: Trowel.

COLOR

14 colors available (see color chart)

VOC

Application temperature: between 12o - 25 oC

APPLICATION RECOMMENDATIONS

Application temperature: between 12o - 25 oC

AMBIENT HUMIDITY

Less than 80%.

APPLY METALLIC EFFECT GEL ON AN ANIMA OR MICROQUARTZ SURFACE

It is recommended to apply a first coat of Metallic Effect Gel as a glaze using the color White Pearl to block the background and allow the subsequent decoration.

DRYING

In normal climatic conditions, at 20°C/60%. approximately 40 minutes.

REPAINTING

2 hours.

REMARKS

Carefully check the preparation of the support, especially that it is free of dust and humidity. Do not leave the containers open for a long period of time and clean the lid and the thread with water or a damp cloth before reusing the product, otherwise the cap may become clogged with the dried product. Apply with good air renewal. Comply with the toxicological norms of the Safety Data Sheet.

RECOMMENDATIONS TO BE TAKEN INTO ACCOUNT DURING THE APPLICATION PROCESS

It is essential to use protective goggles and gloves during the application and mixing process. If the product touches the eyes, wash them immediately with plenty of water and consult an emergency doctor.

CLEANING

The tools should be cleaned with water within the first 30 minutes of use, then mechanical means should be used.

PRESENTATION

Gel Metallic Effect is available in 0,25kg, 1kg and 2kg containers, also available in 0,125gr containers together with the Box Gel Metallic Effect.

STORAGE

At least 12 months in original containers in a dry and protected environment.